



CI Insulating Material Enclosures With Lift-off Cover and Flanges



	Dimensions			Mounting depth	Type Article No.	Price see price list
	Width mm	Height	Depth	mm		
<ul style="list-style-type: none"> • UL listed, CSA approved • Degrees of protection: IEC/EN 60 529: IP 65 NEMA UL 508, CSA C22.2 No. 94: Type 12, 13 4X indoor • Transparent cover, cover fasteners can be sealed • Base RAL 7032 (pebble gray), equipped on all four sides with removable smooth flanges • Mounting bracket for wall mounting 	234	296	150	125	CI23-125-NA 002234	
			175	150	CI23-150-NA 002237	
	421	296	150	125	CI43-125-NA 002238	
			175	150	CI43-150-NA 002241	
		421	150	125	CI43-200-NA 002242	
			175	150	CI44-125-NA 002245	
		796	225	200	CI44-150-NA 002246	
			275	225	CI44-200-NA 002249	
			225	200	CI44-250-NA 002250	
			275	250	CI48-200-NA ¹⁾ 002253	
			275	250	CI48-250-NA ¹⁾ 002254	



Notes:

¹⁾ Type 12, 13 only



CI Insulating Material Enclosures With Hinged Door and Flanges

	Dimensions			Mounting depth mm	Type Article No.	Price see price list
	Width mm	Height	Depth			
<ul style="list-style-type: none"> • UL listed, CSA approved • Degrees of protection: IEC/EN 60 529: IP 65 NEMA UL 508, CSA C22.2 No. 94: Type 12, 13 • Transparent cover, cover fasteners can be sealed • Base RAL 7032 (pebble gray), equipped on all four sides with removable smooth flanges • Mounting bracket for wall mounting, 180° door opening angle 	234	296	166	125	CI23-125/T-NA 002235	
			191	150	CI23-150/T-NA 002236	
 	421	296	166	125	CI43-125/T-NA 002239	
			191	150	CI43-150/T-NA 002240	
			241	200	CI43-200/T-NA 002243	
		421	166	125	CI44-125/T-NA 002244	
			191	150	CI44-150/T-NA 002247	
			241	200	CI44-200/T-NA 002248	
			291	225	CI44-250/T-NA 002251	
		796	241	200	CI48-200/T-NA 002252	
			291	250	CI48-250/T-NA 002255	
			241	200	CI48-200/2T-NA 002256	
		291	250	CI48-250/2T-NA 002257		



Notes:

- Door hinges can be mounted to the left, right, top or bottom as required
- Mounting bracket for wall mounting

CI Insulating Material Enclosures With Lift-off Cover

	Dimensions			Mounting depth mm	Type Article No.	Price see price list		
	Width mm	Height	Depth					
<ul style="list-style-type: none"> • UL listed, CSA approved • Degrees of protection: IEC/EN 60 529: IP 65 NEMA UL 508, CSA C22.2 No. 94: Type 12, 13, 4X indoor • Transparent cover, cover fasteners can be sealed • Base RAL 7032 (pebble gray), with smooth side walls • Mounting bracket for wall mounting 	187.5	250	150	125	CI23X-125-NA 002209			
			175	150	CI23X-150-NA 002212			
		375	250	150	125	CI43X-125-NA 002213		
				175	150	CI43X-150-NA 002232		
			375		225	200	CI43X-200-NA 002217	
					150	125	CI44X-125-NA 002218	
					175	150	CI44X-150-NA 002219	
					225	200	CI44X-200-NA 002220	
				275	250	CI44X-250-NA 002224		

CI Insulating Material Enclosures With Hinged Door

	Dimensions			Mounting depth mm	Type Article No.	Price see price list	
	Width mm	Height	Depth				
<ul style="list-style-type: none"> • UL listed, CSA approved • Degrees of protection: IEC/EN 60 529: IP 65 NEMA UL 508, CSA C22.2 No. 94: Type 12, 13 • Transparent cover, cover fasteners can be sealed • Base RAL 7032 (pebble gray) with smooth side walls • Transparent door with cover locks and 180° door opening angle • Mounting bracket for wall mounting 	187.5	250	166	125	CI23X-125/T-NA 002210		
			191	150	CI23X-150/T-NA 002211		
		375	250	166	125	CI43X-125/T-NA 002214	
				191	150	CI43X-150/T-NA 002215	
				241	200	CI43X-200/T-NA 002216	
				166	125	CI44-125/T-NA 002233	
			191	150	CI44X-150/T-NA 002222		
			241	200	CI44X-200/T-NA 002221		
			291	250	CI44X-250/T-NA 002223		