






## Magnetic Contactors and Starters Field Modification Kits

English / French text	Description	Type Article No.	Price see price list		
<b>Double pushbutton</b>					
 <p>x - removable link</p>	<p>START MARCHÉ</p> <p>STOP ARRÊT</p>	<p>DDL/K11-CS 110315</p> <p>DDL/K11/230-R-CS 110317</p>			
<b>Selector switches</b>					
	<p>OFF ON ARRÊT MARCHÉ</p>	<p>WKV/K10-CS 110319</p> <p>WKV/K11-CS 110321</p>			
	<p>MAN-O-AUTO MAN-O-AUTO</p>	<p>WRK3/K20-CS 110323</p>			
<b>Pilot light</b>					
	<p>Red pilot light, c/w LED element 85 - 264 V AC operating range</p>	<p>L-R/230-R-CS 110325</p>			
	<p>VA Rating VA</p>	<p>Secondary fuse A</p>	<p>Contacteur Size</p>	<p>T...-460/120 Type</p>	<p>Price</p>
<b>Control transformers <sup>1)</sup> including fuse block and fuse</b>					
	50	0.5	DIL(E)EM, DIL00(A)M, DIL0(A)M, DIL1(A)M	T50-230-460/120-PR 180261	
	75	0.75	DIL2(A)M, DILM185, DILM225, DILM250, PKZ2(-SP)	T75-230-460/120-PR 122789	
	100	1.0	DIL3M80, DILM300, DILM400, DILM500	T100-230-460/120-PR 122790	
	150	1.5	DIL4M115	T150-230-460/120-PR 122791	
	250	2.5	DILM580, DILM650, DILM750, DILM820	T250-230-460/120-PR	
	500	5.0		T500-230-460/120-PR 122792	

Note:

<sup>1)</sup> The standard enclosure may or may not have room for the addition of a control transformer.