
















RMQ Titan
Emergency-Stop Buttons, Stop Button

NEMA/UL/CSA 12, 13, 3R, 4X / CE

Pushbuttons and Stacklights






		Contacts N.O. = normally open N.C. = normally closed ⊕ = Positive opening safety function to IEC/EN 60 947-5-1		Color Color of base yellow		Type Article no.	Price See Price List
		N.O.	N.C.	Plunger	Color ¹⁾		
Complete units for surface mounting, IP66, 69K							
Emergency-Stop pushbuttons, tamper proof to ISO 13 850/EN 418 Pull to release Max. number of contacts that can be used: 3 × M22-(C)K...							
 		1	1		● red operator yellow base	M22-PV/KC11/IY-NA 109496	
		-	2		● red operator yellow base	M22-PV/KC02/IY-NA 109497	
Complete units for cover mounting, IP66							
Emergency-Stop pushbuttons, tamper proof to ISO 13 850/EN 418 Pull to release Max. number of contacts that can be used: 4 × M22-(C)K...							
		-	1 ⊕		● red	M22-PV/K01 216515	
		1	1 ⊕		● red	M22-PV/K11 216516	
Emergency-Stop operator		-	-	-	● red	M22-PV 216876	
		-	-	-	● red	M22-PV 216876	
Stop pushbutton operator		-	-	-	● black	M22S-PV 225528	
		-	-	-	● black	M22S-PV 225528	
Emergency-Stop operator illuminated		-	-	-	● red	M22-PVL 216878	
		-	-	-	● red	M22-PVL 216878	
Stop pushbutton operator illuminated		-	-	-	● black	M22S-PVL 230962	
		-	-	-	● black	M22S-PVL 230962	
Emergency-Stop key-release mushroom-head operator, IP66							
With one key	MS1 individual lock mechanisms	-	-	-	● red	M22-PVS 216879	
	MS2 – 20 individual lock mechanisms	-	-	-	● red	M22-PVS-MS* 216880	
Emergency-Stop key-release mushroom-head pushbutton to ISO 13 850/EN 418							
With 1 key, MS1 individual lock mechanism		-	1 ⊕		● red	M22-PVS/K01 216514	
		-	1 ⊕		● red	M22-PVS/K01 216514	

Notes

¹⁾ Red = RAL 3000

RMQ Titan

Emergency-Stop Labels, Sealable Shroud

	Text	Country identifier (as explanation)	Color	Type Article no.	Price See Price List
Emergency-Stop labels, IP66					
Black text, 33 × 50 mm					
	Emergency-Stop	GB	● yellow	M22-XZK-GB99 216472	
	Arrêt d'urgence	F		M22-XZK-F99 216473	
	Not-Aus	D		M22-XZK-D99 216471	
	EMERGENZA	I		M22-XZK-I99 216474	
	Blank	—		M22-XZK 216470	
	With customized inscription ¹⁾			M22-XZK- 216479	
	50 × 50 mm	Four-language		D, GB, F, I	M22-XYK1 216484
	Blank		● yellow	M22-XAK 216464	
	Four-language	D, GB, F, I		M22-XAK1 216465	
	Four-language	D, GB, E, POR		M22-XAK2 216466	
	Four-language	D, GB, NL, F		M22-XAK3 216467	
	Four-language	GB, S, SF, DK		M22-XAK4 216468	
	With customized inscription			M22-XAK- 216469	
	Four-language	D, GB, F, I	M22-XBK1 216483		
	Four-language	D, GB, F, I			
Sealable shroud²⁾, IP65					
				M22-PL-PV 216397	
Protective collar, IP 65	yellow plastic			M22-XGPV 231273	
					

Notes

- ¹⁾ Other languages available upon request - please inquire
Letter height: 5 mm
Number of lines: max. 2
Characters per line: max. 7



- ²⁾ Transparent with collapse point, can be reused after an Emergency-Stop.
For use with M22(S)-PV, M22-PVL, M22-PVS
Adjacent holes in the 30 × 50 mm grid, are to be sealed with M22(S)-B blanking plugs.