

Molded Case Circuit Breakers - Instantaneous Trip
Type NZMH4-...-OBI-...

	Continuous Current Rating	Adjustable Magnetic Trip Range	Type Article No.	Price see price list	Notes:						
	A	A									
Instantaneous trip circuit breakers											
Frame rated at 18A Line and load field-wiring terminals for cable connection supplied as standard					<table border="1"> <thead> <tr> <th>Accessories</th> <th>Page</th> </tr> </thead> <tbody> <tr> <td>Handles</td> <td>09/056</td> </tr> <tr> <td>Accessories</td> <td>09/054</td> </tr> </tbody> </table>	Accessories	Page	Handles	09/056	Accessories	09/054
Accessories	Page										
Handles	09/056										
Accessories	09/054										
up to 480V AC, UL/CSA	2.1	6 - 12	NZMH4-2.1-12-OBI-CNA 031314		Type NZMH4-...-OBI molded case circuit breakers are UL recognized (UL 489) and CSA certified (22.2 Nr. 5.1) instantaneous trip type circuit breakers with an adjustable magnetic trip function. Per NEC, they provide motor short circuit protection as part of a listed combination motor controller that includes coordinated motor overload protection. Short circuit interrupting ratings are, therefore, established and valid only for the listed combination motor controller assembly and associated housing or enclosure.						
	3.7	11 - 20	NZMH4-3.7-20-OBI-CNA 033687								
	6.6	18 - 32	NZMH4-6.6-32-OBI-CNA 036060								
	10	28 - 50	NZMH4-10-50-OBI-CNA 038433								
	12	42 - 80	NZMH4-12-80-OBI-CNA 040806								
	15	64 - 120	NZMH4-15-120-OBI-CNA 043179								
	18	100 - 200	NZMH4-18-200-OBI-CNA 045552								
up to 600Y/347V AC CSA certified only	2.1	6 - 12	NZMH4-2.1-12-OBI-FORMCDN 005466		The NZMH4 instantaneous trip circuit breaker features a current limiting design contact assembly and can provide high fault short circuit current ratings of up to 100kA at 480V AC. Consult Section 03 of this catalog for combination motor controller short circuit ratings as standard starters featuring type NZM instantaneous trip circuit breakers. Consult Moeller Electric for combination motor controller high fault short circuit ratings as motor control center unit starters featuring type NZMH instantaneous trip circuit breakers						
	3.7	11 - 20	NZMH4-3.7-20-OBI-FORMCDN 005467								
	6.6	18 - 32	NZMH4-6.6-32-OBI-FORMCDN 005468								
	10	28 - 50	NZMH4-10-50-OBI-FORMCDN 005469								
	12	42 - 80	NZMH4-12-80-OBI-FORMCDN 005470								
	15	64 - 120	NZMH4-15-120-OBI-FORMCDN 005471								
	18	100 - 200	NZMH4-18-200-OBI-FORMCDN 005472								