










EMR4 Measuring and Monitoring Relays

Level monitoring relays, insulating monitoring relays, sealable shrouds

Description	Input sensitivity	Contact symbol	Supply voltage	Type Article No.	Price see price list
EMR4-N... level monitoring relays					
 <ul style="list-style-type: none"> Monitoring of conductive liquid levels Monitoring mixture proportions of conductive liquids can be set for dry run protection or overflow protection 	5 – 100 kΩ		220 – 240 V AC	EMR4-N100-1-B 221789	
 <ul style="list-style-type: none"> Monitoring of conductive liquid levels Monitoring mixture proportions of conductive liquids Selectable on or off delay 0,5 – 10 s 	250 Ω – 500 kΩ		220 – 240 V AC	EMR4-N500-2-B 221790	
	250 Ω – 500 kΩ		24 – 240 V AC/DC	EMR4-N500-2-A 221791	
Description	Range of dielectric resistance	Contact symbol	Supply voltage	Type Article No.	Price see price list
EMR4-R... insulation monitoring relays					
 <ul style="list-style-type: none"> Monitoring of insulation resistance in ungrounded DC circuits Selector switch for load current or zero-load current Test and reset Status indication via LED 	10 – 110 kΩ		24 – 240 V AC/DC	EMR4-RDC-1-A 221792	
 <ul style="list-style-type: none"> Monitoring of insulation resistance between ungrounded AC circuits and ground conductor Tripping function stored in memory Insulation monitoring in single-phase and three-phase AC circuits Test via test button and remote control Status indication via LED to VDE 0413 part 2 	1 – 110 kΩ		24 – 240 V AC/DC	EMR4-RAC-1-A 221793	
	Module width			Type Article No.	Price see price list
Sealable shroud EMR4-PH...					
	22.5 mm			EMR4-PH22 221795	
	45 mm			EMR4-PH45 221794	