



























RMQ16

UL / CSA / IEC / CE

Illuminated Pushbutton Operators, Contact Elements

		 Square style Front dimensions:							
Lens color		18 × 18 mm	25 × 25 mm	Price	Notes				
		Type	Type	See Price List					
		Article no.	Article no.						
Illuminated pushbutton operators, NEMA 13, IP65									
Momentary Without filament bulb 	 white	Q18LT-WS 089202	Q25LT-WS 086262		 <table border="1" style="width: 100%; margin-top: 20px;"> <thead> <tr> <th>Accessories</th> <th>Page</th> </tr> </thead> <tbody> <tr> <td>Assembly aids and accessories</td> <td>05/064</td> </tr> </tbody> </table>	Accessories	Page	Assembly aids and accessories	05/064
	Accessories	Page							
	Assembly aids and accessories	05/064							
	 green	Q18LT-GN 089067	Q25LT-GN 086206						
	 red	Q18LT-RT 089776	Q25LT-RT 086238						
	 yellow	Q18LT-GE 088808	Q25LT-GE 086173						
 blue	Q18LT-BL 088764	Q25LT-BL 090479							
With filament bulb, 24 V									
 white	Q18LT-WS/WB 088561	Q25LT-WS/WB 090226							
 green	Q18LT-GN/WB 088509	Q25LT-GN/WB 089190							
 red	Q18LT-RT/WB 088537	Q25LT-RT/WB 089998							
 yellow	Q18LT-GE/WB 088449	Q25LT-GE/WB 089137							
 blue	Q18LT-BL/WB 088338	Q25LT-BL/WB 089102							
Maintained Without filament bulb									
 white	Q18LTR-WS 088123	Q25LTR-WS 087232							
 green	Q18LTR-GN 087831	Q25LTR-GN 086812							
 red	Q18LTR-RT 087918	Q25LTR-RT 086840							
 yellow	Q18LTR-GE 087764	Q25LTR-GE 086784							
 blue	Q18LTR-BL 086813	Q25LTR-BL 086739							
With filament bulb, 24 V									
 white	Q18LTR-WS/WB 086708	Q25LTR-WS/WB 086447							
 green	Q18LTR-GN/WB 086413	Q25LTR-GN/WB 086380							
 red	Q18LTR-RT/WB 086448	Q25LTR-RT/WB 086412							
 yellow	Q18LTR-GE/WB 086382	Q25LTR-GE/WB 086346							
 blue	Q18LTR-BL/WB 086348	Q25LTR-BL/WB 086330							
Contact elements^{1) 2)}									
Admissible operational voltage: 5 – 250 V									
	1 N.O.  green	E10 090351	E10 090351						
	1 N.C.⊖  red	E01 090401	E01 090401						

Notes

1) $\begin{matrix} | & xy \\ \backslash & \\ & xy \end{matrix}$ x = Sequence numbers on front element
y = Function numbers on contact element

2) Snaps firmly on the sides of the operator. Blade terminals will accept AMP # 60197-1, 62050-1 or equivalent UL/CSA listed fast-on connectors.

3) UL listed File No. E 29 184
CSA certified File No. 46 552