

Inverse Time Circuit Breakers, 1000 A
Solid State Trip Type NZM12-...-NA

Long time response current setting	Adjustable instantaneous pick-up setting	Adjustable short time delay pick-up setting for selectivity in networks	UL/CSA Interrupting Ratings (AC, 60Hz)	Type	Price	Notes:	
A	A	A	kA RMS sym. at Time delay range: 0 - 1000 ms ²⁾	without handle Article No.	see price list		
Fixed long time response setting							
Frame rated at 1000A Line and load field-wiring terminals for cable connection supplied as standard. ¹⁾							
400	1200 - 12000	-	65 65 50	NZM12-630/ZM12A-400-NA 019857		Accessories Page	
500				NZM12-630/ZM12A-500-NA 080899		Handles 09/084	
600				NZM12-630/ZM12A-600-NA 083272		Accessories 09/082	
700	1600 - 16000			NZM12-800/ZM12A-700-NA 002591		NZM12-.../ZM12(A)-...-NA molded case circuit breakers are UL listed (UL 489) and CSA certified (C22.2 Nr. 5.1) inverse time, solid state trip circuit breakers with a fixed or adjustable long time response and adjustable instantaneous pick-up range.	
800				NZM12-800/ZM12A-800-NA 004964			
1000	2000 - 20000			NZM12-1250/ZM12A-1000-NA 022099			
Adjustable long time response setting							
Frame rated at 1000A Line and load field-wiring terminals for cable connection supplied as standard ¹⁾							
300 - 600	1200 - 12000	-	65 65 50	NZM12-630/ZM12-600-NA 017999		NZM12-.../ZM12V-...-NA molded case circuit breakers are UL listed (UL 489) and CSA certified (C22.2 Nr. 5.1) and have an additional short time delay pick-up range for selectivity in energy distribution networks. The time delay response is adjustable from 0 to 1000ms. ²⁾	
400 - 800	1600 - 16000			NZM12-800/ZM12-800-NA 019083			
500 - 1000	2000 - 20000			NZM12-1250/ZM12-1000-NA 019314			
Adjustable long time response setting and short time delay pick-up for selectivity							
Frame rated at 1000A Line and load field-wiring terminals for cable connection supplied as standard ¹⁾							
300 - 600	1200 - 12000	600 - 7200	65 65 50	NZM12-630/ZM12V-600-NA 019590			
400 - 800	1600 - 16000	800 - 9600		NZM12-800/ZM12V-800-NA 019633			
500 - 1000	2000 - 20000	1000 - 12000		NZM12-1250/ZM12V-1000-NA 019654			

Notes:

¹⁾ Refer to technical data for conductor sizes

²⁾ Time releases: 0, 10, 50, 100, 150, 200, 300, 500, 750, 1000 ms.